

TEC=LED

SNAKE LIGHTS

TEC=LED


LED
SNAKE





Contents Page

Snake Light gets its name from its ability to bend into curved arcs of continuous light. Most models can be bent horizontally or vertically, with some able to bend in both directions.



4 Tiny

Watts / 6W



4 Pygmy

Watts / 6W



4 Threadsnake

Watts / 10W



4 Mini Bidirect

Watts / 10W




5 Taipan

Watts / 5W / 9W



5 Nero

Watts / 5W / 10W / 15W




6 Tiger

Watts / 9W




6 Bidirect

Watts / 10W




6 Free Bend Mamba

Watts / 6.5W / 12W



7 Mamba

Watts / 12W / 15W



7 Sauna Mamba

Watts / 6W



7 Python

Watts / 12W



8 Sauna Python

Watts / 6.5W / 12W




8 Boa

Watts / 12W




9 Mambo XL

Watts
12W / 16.5W



10 Anaconda

Watts / 19W




10 Snake 360° Mini

Watts / 8.6W



10 Snake 360°

Watts / 10W



10 Mounting Options


11 Specifications

TINY

 WATTS 6W	 COLOUR SINGLE	BEAM ANGLE 120°  8mm / 7.2mm 4mm / 6.5mm ● Snake Light ● Standard Extrusion
 VOLTAGE 24vDC	 BEND HORZ	



PYGMY

 WATTS 6W	 COLOUR SINGLE	BEAM ANGLE 120°  6mm / 8.5mm 6mm / 6.1mm ● Snake Light ● Standard Extrusion
 VOLTAGE 24vDC	 BEND VERT	





THREADSNAKE

 WATTS 10W	 COLOUR SINGLE RGB CCT ADJ	BEAM ANGLE 120°  12mm / 13mm 6mm / 8mm ● Snake Light ● Standard Extrusion
 VOLTAGE 24vDC	 BEND HORZ	





MINI BIDIRECT

 WATTS 10W	 COLOUR SINGLE	BEAM ANGLE 120°  Horz: 10mm / 12.4mm Vert: 10mm / 13mm ● Snake Light ● Standard Extrusion
 VOLTAGE 24vDC	 BEND VERT & HORZ	



TAIPAN

 WATTS 5W / 9W	 COLOUR SINGLE	 BEAM ANGLE 120°  Snake Light  Standard Extrusion
 VOLTAGE 24vDC	 BEND VERT & HORZ	





NERO

 WATTS 5W / 10W / 15W	 COLOUR SINGLE	 BEAM ANGLE 120°  Snake Light  Standard Extrusion
 VOLTAGE 24vDC	 BEND HORZ	





TIGER

 WATTS 9W	 COLOUR SINGLE	 BEAM ANGLE 120°  Snake Light  Standard Extrusion
 VOLTAGE 24vDC	 BEND VERT & HORZ	




BIDIRECT

 WATTS 10W	 COLOUR SINGLE	 BEAM ANGLE 120°  Snake Light  Standard Extrusion
 VOLTAGE 24vDC	 BEND VERT & HORZ	





FREE BEND MAMBA

 WATTS 6.5W / 12W	 COLOUR SINGLE	 BEAM ANGLE 120°
 VOLTAGE 24VDC	 BEND VERT & HORZ	 Snake Light Standard Extrusion



MAMBA

 WATTS 12W / 15W	 COLOUR SINGLE RGB RGBW CCT ADJ	 BEAM ANGLE 120°
 VOLTAGE 24VDC	 BEND VERT & HORZ	 Snake Light Standard Extrusion



SAUNA OPTIONS

SAUNA MAMBA

 WATTS 6W	 VOLTAGE 24VDC	 COLOUR SINGLE RGB RGBW CCT ADJ
 BEND / VERT & HORZ		

 BEAM ANGLE 120°	 BEAM ANGLE 120°
 Snake Light Standard Extrusion	 Snake Light Standard Extrusion



BOA

 WATTS 12W	 COLOUR SINGLE RGB RGBW CCT ADJ	 BEAM ANGLE 180°  Snake Light  Standard Extrusion
 VOLTAGE 24vDC	 BEND HORZ	


29mm / 24.8mm
11.5mm / 15.8mm



PYTHON



 WATTS 12W	 COLOUR SINGLE RGB RGBW CCT ADJ	 BEAM ANGLE 180°  Snake Light  Standard Extrusion
 VOLTAGE 24vDC	 BEND HORZ	

21mm / 24.8mm
11.5mm / 15.8mm







SAUNA PYTHON

 WATTS 6.5W / 12W	 VOLTAGE 24vDC	 COLOUR SINGLE RGB RGBW CCT ADJ
 BEND / HORZ		



MAMBO XL

 WATTS 12W / 16.5W	 COLOUR SINGLE RGB RGBW CCT ADJ	 22mm / 26.6mm Horz	 Snake Light  Standard Extrusion
 VOLTAGE 24vDC	 BEND VERT & HORZ	 22mm / 26.6mm 19mm / 26.5mm Vert	BEAM ANGLE 120°




ANACONDA

 WATTS 19W	 COLOUR SINGLE	 20mm / 20mm 30mm / 32mm	 Snake Light  Standard Extrusion
 VOLTAGE 24vDC	 BEND VERT	BEAM ANGLE 120°	





SNAKE 360° MINI

 WATTS 8.6W	 COLOUR SINGLE	BEAM ANGLE 360°  ø13mm x Custom Length	 Snake Light
 VOLTAGE 24vDC	 BEND ROUND 360°		



SNAKE 360°

 WATTS 10W	 COLOUR SINGLE RGB RGBW CCT ADJ	BEAM ANGLE 360°  ø25mm x Custom Length	 Snake Light
 VOLTAGE 24vDC	 BEND ROUND 360°		



CABLE ENTRY OPTIONS

LEFT OR RIGHT SIDE ENTRY



BOTTOM ENTRY




END ENTRY



MOUNTING OPTIONS


ALUMINIUM PROFILE
(STANDARD)



Compatibility	Extrusion Dimensions (mm)		
	Snake	Width	Height
	Tiny	6.5	7.2
	Pygmy	8.5	6.1
	Threadsnake	8	6.1
	Mini Bidirect	13	12.4
	Taipan (HB, VB)	12	13.5
	Nero	17.5	22.9
	Bidirect	20.5	17.6
	Anaconda	32	20

DOUBLE BENDABLE SERRATED
ALUMINIUM PROFILE

(HORIZONTAL AND VERTICAL BEND)



Compatibility	Extrusion Dimensions (mm)		
	Snake	Width	Height
	Taipan (VB)	12	14.5
	Mini Bidirect	11.2	10.3
	Nero	13.5	18
	Bidirect	17.5	16.6

SERRATED ALUMINIUM
PROFILE (STANDARD)



Compatibility	Extrusion Dimensions (mm)		
	Snake	Width	Height
	Taipan (HB, VB)	14.1	14
	Tiger	16	16
	Mamba (HB, VB)	20.2	20.8
	Boa	15.9	24.8
	Python	15.9	24.8
	Mambo XL (HB, VB)	26.6	26.5


FLANGE SERRATED
ALUMINIUM PROFILE



*USE IT WITH OUR SPRING CLIPS.

BENDABLE SERRATED
ALUMINIUM PROFILE

(HORIZONTAL BEND ONLY)



Compatibility	Extrusion Dimensions (mm)		
	Snake	Width	Height
	Boa	15.9	24.8
	Python	15.9	24.8
	Taipan (HB)	14.1	14
	Mamba (HB)	20.2	20.8
	Mambo XL (HB)	26.6	26.5

Compatibility	Extrusion Dimensions (mm)		
	Snake	Width	Height
	Taipan (HB, VB)	21.8	14
	Mamba (HB, VB)	30	20.8
	Boa	25.5	24.8
	Python	25.5	24.8

SELF-CLINCHING
ALUMINIUM
PROFILE

FOR THREE-SIDE SNAKE



BENDABLE
SELF-CLINCHING
ALUMINIUM PROFILE

FOR THREE-SIDE SNAKE



MOUNTING OPTIONS CONTINUE

BENDABLE PVC PROFILE

COLOUR OPTIONS

-  Black
-  White




ROUND CLEAR POLICARBONATE PROFILE

*USE IT WITH OUR CLEAR POLICARBONATE CLIPS.




Compatibility	Extrusion Dimensions (mm)		
	Width	Height	Max
Snake 360° Mini	14.1	13.7	1000



PIVOT MOUNTING BRACKETS




SIDE MOUNTING BRACKETS



SUSPENDED MOUNTING ROD AND CLIP



ROTARY LOCKING BRACKET



SNAKE LIGHTS SPECIFICATIONS

Code/Name	Watts	Bending Direction	Colour	Snake Dimensions	Standard Extrusion Dimensions	IP Rating	Lumens	CRI	Max Length (1 Power Cable)	Cutting Increments	Min. Bending Radius	Material	Dimmable
LSMTINY TINY	6W	HB	2700K, 3000K, 3500K, 4000K, 5500K	4(W) x 8(H)mm x (L)mm	6.5(W) x 7.2(H)mm x Max 1000mm	IP20, IP65	160-182	>90	5m	50mm	ø30mm	Silicone	Triac, Dali, Casambi
LSPYGYMY PYGYMY	6W	VB	2700K, 3000K, 3500K, 4000K, 5000K	6(W) x 6(H)mm x (L)mm	8.5(W) x 6.1(H)mm x Max 1000mm	IP20, IP65, IP67	416-512	>90	5m	25mm	ø50mm	Silicone	Triac, Dali, Casambi
LSTHREAD THREADSNAKE	10W	HB	2700K, 3000K, 3500K, 4000K, 5300K, RGB, CCT Adjustable	6(W) x 12(H)mm x (L)mm	8(W) x 13(H)mm x Max 1000mm	IP20, IP65, IP67	135-292	>90	10m (single colour) 7m (RGB)	50mm	ø120mm	Silicone	Triac, Dali, Casambi
LSMINIBIDIRECT MINI BIDIRECT	10W	HB and VB	2700K, 3000K, 3500K, 4000K, 6500K	10(W) x 10(H)mm x (L)mm	13(W) x 12.4(H)mm x Max 1000mm	IP20, IP65, IP67	397-468	>90	5m	35.7mm	ø300mm	Silicone	Triac, Dali, Casambi
LSTAIPANH,VB TAIPAN	5W	HB or VB	2200K, 2700K, 3000K, 3500K, 4000K, 5700K	10(W) x 10(H)mm x (L)mm	14.1(W) x 14(H)mm x Max 2000mm	IP20, IP65, IP67	195-220	80-90	7.5m	83.3mm	ø100mm	Silicone	Triac, Dali, Casambi
LSTAIPANH,VB TAIPAN	9W	HB or VB	2200K, 2700K, 3000K, 3500K, 4000K, 5700K	10(W) x 10(H)mm x (L)mm	14.1(W) x 14(H)mm x Max 2000mm	IP20, IP65, IP67	390-440	80-90	7.5m	83.3mm	ø100mm	Silicone	Triac, Dali, Casambi
LSNERO NERO	5W / 10W / 15W	HB	2700K, 3000K, 3500K, 4000K	12(W) x 20(H)mm x (L)mm	17.5(W) x 22.9(H)mm x Max 1000mm	IP20, IP65, IP67	47-160	>90	5m	50mm	ø120mm	Silicone	Triac, Dali, Casambi
LSTIGER TIGER	9W	HB or VB	2200K, 2700K, 3000K, 3500K, 4000K, 5700K	12(W) x 12(H)mm x (L)mm	16(W) x 16(H)mm x Max 2000mm	IP20, IP65, IP68	480 (VB) / 420(HB)	80	6m	56mm	ø100mm	Silicone	Triac, Dali, Casambi
LSBIDIRECT BIDIRECT	10W	HB and VB	2700K, 3000K, 3500K, 4000K, 5000K	16(W) x 15(H)mm x (L)mm	20.5(W) x 17.6(H)mm x Max 1000mm	IP20, IP65, IP67	513-565	>90	5m	50mm	ø200mm	Silicone	Triac, Dali, Casambi
LSFREEMAMBA FREE BEND MAMBA	6.5W	HB and VB	2200K, 2700K, 3000K, 3500K, 4000K, 5700K	16(W) x 17(H)mm x (L)mm	20.6(W) x 25(H)mm x Max 1000mm	IP20, IP65, IP68	420	80	10m	55.6mm	ø300mm	Silicone	Triac, Dali, Casambi
LSFREEMAMBA FREE BEND MAMBA	12W	HB and VB	2200K, 2700K, 3000K, 3500K, 4000K, 5700K	16(W) x 17(H)mm x (L)mm	20.6(W) x 25(H)mm x Max 1000mm	IP20, IP65, IP68	840	80	10m	55.6mm	ø300mm	Silicone	Triac, Dali, Casambi
LSMAM-BAVB,HB MAMBA	12W	HB or VB	2200K, 2700K, 3000K, 3500K, 4000K, 4500K, 5000K, 5700K, RGB, RGBW, CCT Adjustable, Dim to Warm	16(W) x 17(H)mm x (L)mm	20.2(W) x 20.8(H)mm x Max 2000mm	IP20, IP65, IP68	220-580	80-90	10m (single colour) 7m (RGB) 5m (RGBW)	55.6mm (Single Colour) 83.3mm (RGB)	ø300mm	Silicone	Triac, Dali, Casambi
LSMAM-BAVB,HB MAMBA	15W	HB or VB	2200K, 2700K, 3000K, 3500K, 4000K, 5700K, RGB, RGBW, CCT Adjustable, Dim to Warm	16(W) x 17(H)mm x (L)mm	20.2(W) x 20.8(H)mm x Max 2000mm	IP20, IP65, IP68	500-800	80-90	10m (single colour) 7m (RGB) 5m (RGBW)	55.6mm (Single Colour) 83.3mm (RGB)	ø300mm	Silicone	Triac, Dali, Casambi
LS3SMAMBA THREE SIDED MAMBA	12W	VB	2200K, 2700K, 3000K, 3500K, 4000K, 5700K, RGB, RGBW, CCT Adjustable	16(W) x 17(H)mm x (L)mm	17.8(W) x 10.5(H)mm x Max 2000mm	IP20, IP65, IP68	850-1100	80-90	10m (single colour) 7m (RGB) 5m (RGBW)	55.6mm (Single Colour) 83.3mm (RGB)	ø300mm	Silicone	Triac, Dali, Casambi
LSSAUNAMAM-BA SAUNA MAMBA	6W	HB or VB	2200K, 2700K, 3000K, 3500K, 4000K, 5700K, RGB, RGBW, CCT Adjustable, Dim to Warm	16(W) x 17(H)mm x (L)mm	20.2(W) x 20.8(H)mm x Max 2000mm	IP67	350	80-90	10m (single colour) 7m (RGB) 5m (RGBW)	55.6mm (Single Colour) 83.3mm (RGB)	ø300mm	Silicone	Triac, Dali, Casambi
LSPYTHON PYTHON	12W	HB	2200K, 2700K, 3000K, 3500K, 4000K, 5700K, RGB, RGBW, CCT Adjustable, Dim to Warm	11.5(W) x 21(H)mm x (L)mm	15.9(W) x 24.8(H)mm x Max 2000mm	IP20, IP65, IP68	170-340	80-90	10m (single colour) 7m (RGB) 5m (RGBW)	83.3mm (Single Colour) 100mm (RGB)	ø120mm	Silicone	Triac, Dali, Casambi
LSSAUNAPYTHON SAUNA PYTHON	6W	HB	2200K, 2700K, 3000K, 3500K, 4000K, 5700K, RGB, RGBW, CCT Adjustable, Dim to Warm	11.5(W) x 21(H)mm x (L)mm	15.9(W) x 24.8(H)mm x Max 2000mm	IP67	210	80-90	10m (single colour) 7m (RGB) 5m (RGBW)	83.3mm (Single Colour) 100mm (RGB)	ø120mm	Silicone	Triac, Dali, Casambi
LSBOACCT BOA	12W	HB	2200K, 2700K, 3000K, 3500K, 4000K, 5700K, RGB, RGBW, CCT Adjustable, Dim to Warm	11.5(W) x 29(H)mm x (L)mm	15.9(W) x 24.8(H)mm x Max 2000mm	IP20, IP65, IP68	230-470	80-90	10m (single colour) 7m (RGB) 5m (RGBW)	83.3mm (Single Colour) 100mm (RGB)	ø120mm	Silicone	Triac, Dali, Casambi
LSMAMBOXLVB MAMBO XL	12W	VB	2200K, 2700K, 3000K, 3500K, 4000K, 5700K, RGB, RGBW, CCT Adjustable, Dim to Warm	22(W) x 19(H)mm x (L)mm	26.6(W) x 26.5(H)mm x Max 2000mm	IP20, IP65, IP68	300-950	>80	10m (single colour) 7m (RGB) 5m (RGBW)	50mm	ø400mm	Silicone	Triac, Dali, Casambi
LSMAMBOXLHB MAMBO XL	12W	HB	2200K, 2700K, 3000K, 3500K, 4000K, 5700K, RGB, RGBW, CCT Adjustable, Dim to Warm	22(W) x 22(H)mm x (L)mm	26.6(W) x 26.5(H)mm x Max 2000mm	IP20, IP65, IP68	300-950	>80	10m (single colour) 7m (RGB) 5m (RGBW)	50mm	ø400mm	Silicone	Triac, Dali, Casambi
LSMAMBOXLVB MAMBO XL	16.5W	VB	2200K, 2700K, 3000K, 3500K, 4000K, 5700K	22(W) x 19(H)mm x (L)mm	26.6(W) x 26.5(H)mm x Max 2000mm	IP20, IP65, IP68	950-1400	>80	10m (single colour)	50mm	ø400mm	Silicone	Triac, Dali, Casambi
LSMAMBOXLHB MAMBO XL	16.5W	HB	2200K, 2700K, 3000K, 3500K, 4000K, 5700K	22(W) x 22(H)mm x (L)mm	26.6(W) x 26.5(H)mm x Max 2000mm	IP20, IP65, IP68	950-1400	>80	10m (single colour)	50mm	ø400mm	Silicone	Triac, Dali, Casambi
LSANACONDA ANACONDA	19W	VB	2700K, 3000K, 3500K, 4000K, 5500K	30(W) x 20(H)mm x (L)mm	32(W) x 20(H)mm x Max 1000mm	IP20, IP65, IP67	1005-1089	>93	5m	50mm	ø300mm	Silicone	Triac, Dali, Casambi
LS360SNAKE-MINI SNAKE 360° MINI	8.6W	Round 360°	2700K, 3000K, 3500K, 4000K	ø13mm x (L)mm	14.1(W) x 13.7(H) x Max 1000mm	IP20, IP65	386-400	>90	5m	25mm	ø150mm	Silicone	Triac, Dali, Casambi
LS360SNAKE SNAKE 360°	10W	Round 360°	2700K, 3000K, 3500K, 4000K, RGB, RGBW, CCT Adjustable	ø25mm x (L)mm	30(W) x 27.4(H) x Max 1000mm	IP20, IP65	193-744	>90	5m	50mm	ø200mm	Silicone	Triac, Dali, Casambi



TEC=LED

TecLED Pty Ltd - Sydney Head Office

Unit 4, 61 - 71 Beauchamp Road,
Matraville NSW 2036

Telephone: (02) 9317 4177

Email: sales@tecled.com.au

TecLED Pty Ltd – Melbourne*

Level 1, 167-169 Moray Street,
South Melbourne VIC 3205

Telephone: 0478 036 481

Email: vicsales@tecled.com.au

TecLED Pty Ltd – Gold Coast*

Telephone: 0425 298 712

*Showroom by appointment only