

ZELA Deep Fixed Downlight



- IP65 (front face)
- Size 82x57mm
- Cut-out 73mm
- Min hole depth* 67mm

*Specification is for ceiling material ≤ 13mm.



Lens diffuser
Beam 9° 15° 20°
Spot lighting



Prismatic diffuser
Beam 40° 55°
General lighting

Trim options:



Textured white



Textured black

*9° only available in CRI 97

*9° & 15° only available in CCT 2700K, 3000K or 4000K

FITTING TYPE	CODE	W	BEAM ANGLE/LUMENS					IC	CCT	CUT-OUT	CRI	DIMMABLE	DIMENSIONS DIA x Height
			9°	15°	20°	40°	55°						
DEEP FIXED	DLZDFIXED4.3W	4.3W	260 - 280	290 - 320	350 - 400	370 - 430	360 - 420	4	2400K 2700K 3000K 4000K	Ø73mm	>90	TRIAC DALI	82 x 57mm
	DLZDFIXED7.7W	7.7W	370 - 400	480 - 520	570 - 670	610 - 710	600 - 700	n/a					
	DLZDFIXED11W	11W	n/a	640 - 700	760 - 890	810 - 940	800 - 930	n/a					
DEEP FIXED S-DIM	DLZDFIXED7.7WSD	7.7W	40°		55°			4	3000-1850K				
	DLZDFIXED11WSD	11W	530		520			n/a					



Warranty
5yr Driver



Get in touch

U4 / 61-71 Beauchamp Rd,
Matraville NSW 2036

02 9317 4177
0425 350 698

sales@tecled.com.au
Victoria@tecled.com.au

Follow us

